

AUCMA

QINGDAO AUCMA IMPORT AND EXPORT CO.,LTD.

No.1 Building , Aucma Smart Industrial Park, Laoshan District, Qingdao, China

Tel: 86-532 88966289(Asia-Pacific Division 1)
86-532 88966271(Asia-Pacific Division 2)
86-532 88966255(America Division)
86-532 88966295(Africa Division)
86-532 88966297(Middle-East /Europe Division)
86-532 88966276(E-Commerce)
E-mail: kushuchun@aucma.com.cn
Website: www.aucmaoverseas.com



(2022)

AUCMA



COMMERCIAL COLD CHAIN OF AUCMA



BRIEF INTRODUCTION

Aucma Co., Ltd. was established in 1987 and got listed on Shanghai Stock Exchange on December, 2000. Always aiming to be the most reliable refrigeration equipment supplier and refrigeration expert of the world.

With the development of people's living standard, increasing demand to commercial cold chain products was increasing rapidly. Aucma commercial refrigeration division realized fast growing during the past 10 years and become the leading domestic supplier of commercial refrigeration. 1.2 million units sales was achieved in 2020.

With 35-year development, Aucma has become full commercial cold chain supplier including cooler, freezer, vending machine, cold room, kitchen refrigerator, supermarket freezer and refrigerator truck. Cooler ranged from 60L to 1500L, counter top, single door and multi-door products. Commercial freezer ranged full curved lids, flat lids, combination freezer, island freezer and integral freezer.

Aucma commercial refrigeration partnered with 8000 clients globally, including Coca-Cola, AB-Inbev, Danone, Nongfu Spring, Yuanqi Forest, Yili dairy, Uni president etc.. Covered full domestic beverage, beer, dairy, ice cream and restaurant business. Cooperate with overseas customers from nearly 100 countries.

A strong R&D team was the core to win market. Aucma commercial refrigeration division has more than 280 professional engineers with average experience 10-year in this field. Besides, 6 million USD was spent to build our own global innovation test center, covered 4500 M2. It's CNAS approved lab, test report acceptable by VDE, UL, CSA and CCC.

Aucma industrial park was put into use since 1995, covered 530,000 M2. The designed production capacity of freezer can reach 3 million units annually. For cooler, it can reach 1.5 million units annually. 5-year working experience on average for core assembly team of commercial refrigeration production line to ensure good reliability and stability.

With abundant experience in commercial refrigeration field, our mission is to meet every customer with their own customization solution. We have experts on different markets, structure design, refrigeration system, function innovation and manufacturing. Propose your idea to work with our experts!





CONTENTS

BEVERAGE COOLER

- 07-07 ♦ COUNTER TOP
- 08-09 ♦ STATIC COOLING
- 10-11 ♦ VENTILATED
- 12-12 ♦ HIGH-END
- 13-13 ♦ 4-SIDE GLASS DOOR
- 14-14 ♦ SLIM LINE
- 15-16 ♦ MULTI-DOOR

COMMERCIAL FREEZER

- 17-20 ♦ CURVED LIDS
- 21-21 ♦ FLAT LIDS
- 22-22 ♦ HIGH-END
- 23-23 ♦ VERTICAL DISPLAY
- 24-24 ♦ COMBINATION FREEZER
- 25-25 ♦ INTEGRAL FREEZER
- 26-26 ♦ ISLAND FREEZER

SUPERMARKET FREEZER

- 29-29 ♦ REMOTE OPEN COOLING MULTIDECK
- 30-30 ♦ REMOTE FREEZING MULTIDECK WITH GLASS DOOR
- 31-31 ♦ 850 SERIES ISLAND FREEZER
- 32-32 ♦ 830 SERIES ISLAND FREEZER
- 33-33 ♦ SERVICE COUNTER
- 34-34 ♦ PLUG IN SEMI MULTIDECK
- 35-36 ♦ PLUG IN OPEN FRONT COOLER
- 37-37 ♦ STORAGE FREEZER
- 38-38 ♦ PLUG-IN GLASS DOOR COOLER

SPECIFICATION

- 39-45 ♦ SPECIFICATION



BUILT-IN LARGE FAN

360 degree refrigeration

Cooling evenly fast



DOUBLE HOLLOW GLASS DOORS

Strong disassembled gasket


Have design of multi-temperature zone, conserve food by classification scientifically & healthily. Different foods have their single spaces.



ADJUSTABLE SHELF

Dip plastic steel wire grid

Break the limitation of freezer. Freezing is easy & free.



ELECTRONIC THERMOSTAT

Electronic thermostat, easy to operate

adjust temperature quickly cooling quickly freezing. Holiday ECO Mode is ready for chosen, other function is power off memory



SAFETY DOOR LOCK DESIGN

New lock design for security door

Open alarm, Faculty prompt & child - lock



ALUMINUM ALLOY HANDLE

Recessed hidden handle

Door gasket is made up of many gasbags. Keep cool air inside & conserve temperature. Save energy. The door gasket is detachable & easy to clean.





SC-65



SC-85



SC-115

model:

SC-65/85/115
SC/GH-115



CFC free



Canopy removable

Feature:


Double-pane glass door,
Mechanical thermostat
Branded canopy removable (except SC-65)
Interior LED lighting
Heating function (for SH-115)

Parameter:

Model	SC-65	SC-85	SC-115	SC/GH-115
Net Volume	L 65	85	115	115
Facing (330mm)	Can 5	5	5	5
Product dimensions (W*D*H)	mm 470×535×685	470×535×(812+180)	470×535×(1017+180)	470×535×(1017+180)
Package dimensions (W*D*H)	mm 530×595×715	530×595×855	530×595×1060	530×595×1060
Stuffing quantity 40H	Set 258	258	172	172



SC-106/246/286/336



SC-385



SC-281GA/341GA

model:

SC-106/246/286/336
SC-385
SC-281GA/341GA



CFC free



Canopy removable



Roll bond evaporator

Feature:

Roll-bond evaporator model
Double-pane glass door, with Low-E film
Digital thermometer (except SC-385)
Canopy removable (except SC-281GA/341GA)
Interior LED lighting

Parameter:

Model	SC-106	SC-246	SC-286	SC-385	SC-385	SC-281GA	SC-341GA
Net Volume	106	240	300	340	286	340	305
Facing (330mm)	5	7	7	7	8	7	7
Product dimensions (W*D*H)	470X520X(1102+202/660X550X(1348+251)	560X550X(1529+253)	560X560X(1704+253)	645+618+2055	595*555*1895	595*555*2000	
Package dimensions (W*D*H)	535X595X1150	621X628X1403	625X625X1580	625X665X1755	707X685X2105	652*624*1927	652*624*2032
Stuffing quantity 40H	160	104	57	57	51	57	57

STATIC COOLING



CFC free



Built-in evaporator



Aluminum inner liner

model :

SC-209E/229E/279E/329E
SC-387

Feature:

Build-in evaporator model
Double-pane glass door
Mechanical thermostat
Aluminum inner liner
Interior LED lighting

Parameter :

Model	SC-209E	SC-229E	SC-279E	SC-329E	SC-387
Net Volume	L	195	212	267	301
Facing	330mm Can	6	6	7	8
External dimensions (W*D*H)	mm	525*550*1857	520*550*1852	595*550*1737	595*570*1842
Package dimensions (W*D*H)	mm	562*624*1589	562*624*1684	652*624*1769	652*624*1874
Stuffing quantity 40H	Set	106	104	76	76

VENTILATED



SC-380



SC-281C
SC-341C



SC-386
SC-388
SC-400



SC-528
SC-606

model :

SC-380
SC-281C/341C
SC-386/388/400
SC-528/606

Feature:

Fin-type evaporator model
Double-pane glass door, with Low-E film
Mechanical & digital thermostat for option
Air cooling, no frost
Interior LED lighting



CFC free



Fin-type evaporator



Air cooling

Parameter :

Model	SC-380	SC-281C	SC-341C	SC-386	SC-388	SC-400	SC-528	SC-606
Net Volume	L	305	266	306	386	388	430	528
Facing	330mm Can	7	7	7	8	8	8	10
External dimensions (W*D*H)	mm	595*555*2000	595*555*1896	595*555*2000	680*685*2120	660*665*2220	660*680*2135	756*675*2294
Package dimensions (W*D*H)	mm	652*624*2032	652*624*1927	652*624*2032	725*755*2160	725*755*2280	725*765*2165	857*757*2315
Stuffing quantity 40H	Set	57	57	57	48	48	48	42



SC-360A



SC-360NA

model:

SC-360A/ SC-320NA/SC-360NA/
SC-480NA



CFC free



Fin-type
evaporator



Air cooling

Feature:

Double pane glass door
No canopy model (except SC-360W)
Metal inner liner for long life
Vertical double door for SC-360W
Economic air-cooling model, no frost

Parameter:

Model		SC-360A	SC-320NA	SC-360NA	SC-480NA
Net Volume	L	360	320	360	480
Facing	330ml Can	7	7	7	7
External dimensions (W*D*H)	mm	600 X 565 X 1915	600x565x1640	600x565x1730	610x724x1845
Package dimensions (W*D*H)	mm	650X 610 X 1980	650x610x1700	650x610x1790	660x775x1910
Stuffing quantity 40H	Set	76	77	76	69



CFC free



Fin-type
evaporator



Air cooling

model:

SC-400HA/SC-510/SC-540/
SC-620/SC-760

Feature:

Frameless glass door with metal strip
Step compartment for more display (except
SC-400HA and SC-540)
Round corners for integrative appearance
Customization LED Logo on glass door
Air cooling, extreme energy saving model

Parameter:

Model		SC-400HA	SC-510	SC-540	SC-620	SC-760
Net Volume	L	400	278	378	504	760
Facing	330ml Can	8	8	9	9	12
External dimensions (W*D*H)	mm	660*683*1880	680*657*2098	730*680*2145	730*652*2137	897*652*2137
Package dimensions (W*D*H)	mm	725*765*1970	741*769*2132	828*750*2240	962*738*2190	962*738*2190
Stuffing quantity 40H	Set	47	48	42	36	36



model:

SC-42A/SC-62A/SC-130A/
SC-178A/SC-239A



CFC free



Fin-type
evaporator



Air cooling

Feature:

4-side glass door for better display
4-side vertical LED lighting
Bottom integral foaming for better stability
Various size selectable
Digital thermostat control

Parameter:

Model		SC-42A	SC-62A	SC-130A	SC-178A	SC-239A
Net Volume	L	40	60	130	178	240
Facing	330ml Can	4	4	6	6	6
External dimensions (WxDxH)	mm	370*406*930	370*406*900	500*535*1100	500*535*1323	500*535*1600
Package dimensions (WxDxH)	mm	440*478*700	440*478*870	570*605*1170	570*605*1393	570*605*1673
Stuffing quantity 40H	Set	665	399	156	78	78



CFC free



Fin-type
evaporator



Air cooling

model:

SC-160W
SC-260/260D

Feature:

Slim line for smaller foot-print area
Fin-type evaporator model
Double-pane glass door, with Low-E film
Mechanical & digital thermostat for option
Air cooling, no frost

Parameter:

Model		SC-160W	SC-260D	SC-260
Net Volume	L	160	260	260
Facing	330ml Can	4	5	5
External dimensions (WxDxH)	mm	390*485*1885	470*570*1866	470*700*1893
Package dimensions (WxDxH)	mm	440*530*1920	530*650*1940	530*745*2068
Stuffing quantity 40H	Set	139	76	66



model:

SC-409/609/809
SC-800/1200
SC-1006



Parameter:

Model		SC-409	SC-609	SC-809	SC-800	SC-1200	SC-1006
Net Volume	L	390	577	778	800	1200	905
Facing	330ml Can	10	14	16	14	21	16
External dimensions (WxDxH)	mm	890x587x1897	1180x587x1893	1430x657x1903	1180x625x2000	1780x625x2000	1200x715x2250
Package dimensions (WxDxH)	mm	1000x650x2052	1290x650x2132	1540x750x2052	1260x725x2105	1890x725x2105	1275x785x2430
Stuffing quantity 40H	Set	41	27	22	27	19	24


Feature:

Double-door or triple-door cooler
Double-pane glass door, with Low-E film
Mechanical & digital thermostat for option
Metal inner liner for longer life
Aluminum frame



model:

SC-800HA/1000HA/1100HA/1200HA/1300HA
/1400HA/1800HA
SC-800SA/1000SA/1100SA/1200SA
/1300SA/1400SA/



Parameter:

Model		SC-800HA	SC-800SA	SC-1000HA	SC-1000SA	SC-1100HA	SC-1100SA	SC-1200HA	SC-1200SA
Net Volume	L	790	873	870	772	954	823	1074	
Facing	330ml Can	12	12	12	12	14	14	14	
External dimensions (WxDxH)	mm	1000x680x2020	1000x660x2020	1000x700x2020	1000x730x2020	1200x680x2020	1200x660x2020	1200x750x2020	
Package dimensions (WxDxH)	mm	1045x785x2085	1045x685x2085	1045x775x2085	1045x775x2085	1245x705x2085	1245x685x2085	1245x775x2085	
Stuffing quantity 40H	Set	33	33	33	33	28	28	27	
Model		SC-1200HA	SC-1300HA	SC-1300SA	SC-1400HA	SC-1400SA	SC-1800HA		
Net Volume	L	943	1101	950	1245	1093	1600		
Facing	330ml Can	14	16	16	16	16	21		
External dimensions (WxDxH)	mm	1200x660x2020	1375x660x2020	1375x660x2020	1375x750x2020	1375x750x2020	1800x730x2020		
Package dimensions (WxDxH)	mm	1245x685x2085	1420x685x2085	1420x685x2085	1420x775x2085	1420x775x2085	1845x755x2085		
Stuffing quantity 40H	Set	28	24	24	24	24	19		

Feature:

Air cooling model, no frost
Double-pane glass door, self-closing
Opening door or sliding door for option
Digital thermostat
Self evaporating drip tray



SD-152



SD-180



SD-280



SD-330/338HA/420/520

model:

SD-152/180/280/330/338HA/420/520



CFC free


Optional inner
liner material

Professional
drainage design

Feature:

Curved sliding lids with Low-E film
PCM or Aluminum inner liner for option
Integrated cabinet frame
Professional drainage design
Mechanical & digital thermostat for option

Parameter:

Model	SD-152	SD-180	SD-280	SD-330	SD-338HA	SD-420	SD-520
Net Volume	L	118L	122L	177L	214L	256L	345L
Baskets Number	EA	2	3	4	5	5	7
External dimensions (W*D*H)	mm	584*604*927	756*656*945	986*656*975	1224*654*920	1234*654*925	1315*696*939
Package dimensions (W*D*H)	mm	662*772*1022	838*736*910	1085*736*940	1303*736*950	1303*736*1025	1369*776*990
Stuffing quantity 40H	Set	158	126	99	81	54	72



SD-289/359



SD-439/519

model:

SD-289/359/439/519



CFC free


Optional inner
liner material

Optional frame
material

Professional
drainage design

Feature:

Curved sliding lids with Low-E film
PCM or Aluminum inner liner for option
Aluminum & ABS cabinet frame
Professional drainage design
Mechanical & digital thermostat for option

Parameter:

Model	SD-289	SD-359	SD-439	SD-519
Net Volume	L	202L	248L	322L
Baskets Number	EA	4	5	6
External dimensions (W*D*H)	mm	1049*695*920	1229*695*920	1493*695*920
Package dimensions (W*D*H)	mm	1127*773*1009	1303*773*1009	1571*773*1009
Stuffing quantity 40H	Set	90	81	63



model:

SD220Q/SD320Q/SD420Q/SD520Q/
SD620Q/SD720Q

Feature:

Curved sliding lids with Low-E film
 Precoated Aluminum inner liner
 Aluminum & ABS cabinet frame
 Anti dew pipe design
 Mechanical & digital thermostat for option



CFC free

Anti dew pipe
designOptional frame
materialLight box
optional

Parameter:

Model		SD220Q	SD320Q	SD420Q	SD520Q	SD620Q	SD720Q
Net Volume	L	156	212	278	350	427	480
Baskets Number	EA	2	3	4	5	6	7
External dimensions (W*D*H)	mm	740x680x850	1030x680x850	1270x680x850	1530x680x850	1810x680x850	2000x675x850
Package dimensions (W*D*H)	mm	790x780x890	1080x780x890	1320x790x890	1580x780x890	1800x790x890	2060x770x890
Stuffing quantity 40H	Set	134	98	79	65	56	51



model:

SDQ300/SDQ400/SDQ500/
SDQ600/SDQ700

Feature:

Double curved sliding lids with Low-E film
 Precoated Aluminum inner liner
 Aluminum & ABS cabinet frame
 Anti dew pipe design
 Mechanical & digital thermostat for option



CFC free

Anti dew pipe
designOptional frame
materialLight box
optional

Parameter:

Model		SDQ300	SDQ400	SDQ500	SDQ600	SDQ700
Net Volume	L	273L	355L	445L	545L	645L
Baskets Number	EA	3	4	5	6	7
External dimensions (W*D*H)	mm	1000x695x850	1250x695x850	1500x695x850	1750x695x850	2000x695x850
Package dimensions (W*D*H)	mm	1050x750x890	1300x750x890	1550x750x890	1800x750x890	2050x750x890
Stuffing quantity 40H	Set	98	80	66	56	50



model:

SD-100F/200F/300F/400F/500F/600F

CFC

CFC free



Optional inner liner material

Feature:

Flat sliding lids with Low-E film
PCM or Aluminum inner liner for option
ABS cabinet frame
Professional drainage design
Mechanical & digital thermostat for option

Parameter:

Model	SD-100F	SD-200F	SD-300F	SD-400F	SD-500F	SD-600F
Net Volume	L 77L	156L	215L	275L	337L	403L
Baskets Number	EA 1	1	1	1	1	1
External dimensions (WxDxH)	mm 600*522*825	934*574*825	1014*604*825	1222*694*825	1434*694*825	1664*694*825
Package dimensions (WxDxH)	mm 660*582*885	994*634*885	1094*724*885	1302*774*885	1514*774*885	1744*774*885
Stuffing quantity 40H	Set 215	108	95	81	72	57



model:

SD-435/SD-525/SD-665

CFC

CFC free



Interior LED lighting

Feature:

TEC7 glass door for better heat insulation and condensation prevention
Micro-arc, 3-side frameless glass door for more display
Handle aligned with frame totally for more display
Two-side water drain pan to prevent overflow
Extreme energy-saving model

Parameter:

Model	SD-435	SD-525	SD-665
Net Volume	L 310	395	510
Shelves number	EA 6	6	6
External dimensions (WxDxH)	mm 1350*690*880	1660*690*880	1850*796*880
Package dimensions (WxDxH)	mm 1430*778*925	1751*778*940	1925*875*930
Stuffing quantity 40H	Set 48	40	28

VERTICAL DISPLAY

COMBINATION FREEZER



Model:

SD-100 SDQ-160S
SD-368 SDQ-400S
SD-1000D SDQ-1600M



CFC free



Vertical display



Air cooling

Parameter:

Model		SD-100	SD-368	SDQ-160S	SDQ-400S	SD-1000D	SDQ-1600M
Net Volume	L	100L	290L	148	380	975	1400
Shelves number	EA	2	4	5	5	10	15
External dimensions (W*D*H)	mm	600*605*940	660*711*2170	390*505*1885	670*665*2010	1220*865*2010	1800*730*2020
Package dimensions (W*D*H)	mm	600*620*1050	725*755*2217	440*530*2100	700*655*2030	1250*855*2030	1845*755*2085
Stuffing quantity 40H	Set	104	48	139	51	27	16

Feature:

Vertical display freezer
Branded canopy
Triple-pane glass door with Low-E film
Air cooling, no frost
Digital thermostat



SD-426WT



SD-536T



SCD-396/506



SCD-436/606T

model:

SD-326/426WT/536T
SCD-436/606T
SCD-396/506



CFC free



Top freezer or cooler optional

Feature:

Combination freezer for smaller foot-print area
Top freezer or cooler for different application
Up & down sliding lids with Low-E film
Professional drainage design
Mechanical & digital thermostat for option

Parameter:

Model	SD-326	SD-426WT	SD-536T	SD-436	SD-606T	SCD-396	SCD-596
Net Volume	L	200L	200L	360L	450L	316L (132+184)	405L (172+233)
Baskets Number	EA	6	5	6	6	8	3
External dimensions (W*D*H)	mm	1250*600*1110	1250*790*1025	1500*940*1025	1800*970*1080	1800*960*1040	952*700*1880
Package dimensions (W*D*H)	mm	1315*662*1246	1330*870*1130	1575*980*1130	1820*912*1246	1800*770*1150	1101*820*1996
Stuffing quantity 40H	Set	48	42	26	36	36	28

INTEGRAL FREEZER



SD-561/661/761/1021



SD-602/702

model:

SD-561/661/761/1021
SD-602/702



CFC free



Interior LED lighting

Feature:

Integral freely for different application
PCM inner liner for easy defrost
Front curved sliding lids with Low-E film
Interior LED lighting
Professional drainage design

Parameter:

Model		SD-561	SD-661	SD-761	SD-1021	SD-602	SD-702
Net Volume	L	411L	479L	549L	715L	440L	515L
Baskets Number	EA	6	6	6	6	6	6
External dimensions (W*D*H)	mm	1651*173*40	1811*173*40	16511*1017*340	20511*1017*340	1895796*777	1895796*777
Package dimensions (W*D*H)	mm	1705*875*930	1925*875*930	17051075*940	21051075*1045	2008*891*905	2008*891*905
Stuffing quantity 40H	Set	28	24	28	20	26	26

ISLAND FREEZER



SD-532



SD-570/SD-528



SD-575/SD-728

model:

SD-532/570/528/575/728



CFC free



T type



Reinforced baskets



Aluminum alloy round corner

Feature:

T type island freezer
Flat sliding lids with Low-E film
Reinforced baskets for more frozen foods
Aluminum alloy round corner design
Castor for option to be movable

Parameter:

Model		SD-532	SD-570	SD-528	SD-575	SD-728
Net Volume	L	364L	425L	381L	391L	516L
Baskets Number	EA	6	6	6	6	6
External dimensions (W*D*H)	mm	187*191*919	187*823*908	187*823*968	1997*1023*788	1997*1023*968
Package dimensions (W*D*H)	mm	1923*969*1060	1923*969*1005	1923*969*965	2043*1069*885	2043*1069*1060
Stuffing quantity 40H	Set	24	24	24	33	22




REMOTE OPEN COOLING MULTIDECK



model: RVM-201309 RVM-201909 RVM-202509 RVM-203809 RVM-201709EC
RVM-201309V RVM-201909V RVM-202509V RVM-203809V RVM-201709ECV

Feature:

- Digital thermostat for exact temperature control
- Bigger capacity within same covered area
- Squeeze air curtain design to provide uniform cooling
- Glass or mirror side board for option



Parameter:

Model	External dimensions/mm	Package dimensions/mm	Temperature range/°C	Gross volume/L	Display area/m ²	Stuffing quantity 40HC
RVM-201309	1250*850/870*2000	1370*970/990*2080	-1°C~-5°C	900	2.01	17
RVM-201909	1875*850/870*2000	1995*970/990*2080	-1°C~-5°C	1350	3.02	12
RVM-202509	2500*850/870*2000	2620*970/990*2080	-1°C~-5°C	1800	4.02	8
RVM-203809	3750*850/870*2000	3870*970/990*2080	-1°C~-5°C	2700	6.03	6
RVM-201709EC	1700*850/870*2000	1820*970/990*2080	-1°C~-5°C	1220	2.14	13

Doored Remote Open Cooling Multideck

Model	External dimensions/mm	Package dimensions/mm	Temperature range/°C	Gross volume/L	Display area/m ²	Stuffing quantity 40HC
RVM-201309V	1250*850/870*2000	1370*970/990*2080	-1°C~-5°C	900	1.58	17
RVM-201909V	1875*850/870*2000	1995*970/990*2080	-1°C~-5°C	1350	2.37	12
RVM-202509V	2500*850/870*2000	2620*970/990*2080	-1°C~-5°C	1800	3.17	8
RVM-203809V	3750*850/870*2000	3870*970/990*2080	-1°C~-5°C	2700	4.75	6
RVM-201709ECV	1700*850/870*2000	1820*970/990*2080	-1°C~-5°C	1220	2.15	13


REMOTE FREEZING MULTIDECK WITH GLASS DOOR



model: RVF-201509V RVF-202309V RVF-203009V
RVD-201509V RVD-202309V RVD-203009V

Feature:

- Bigger display area
- Digital thermostat for exact temperature control
- Interior low noise design
- Triple-pane glass door with electrical heater



Parameter:

Type	Model	External dimensions/mm	Package dimensions/mm	Temperature range/°C	Gross volume/L	Display area/m ²	Stuffing quantity 40HC
Freezing	RVF-201509V	1500*860*2000	1620*860*2080	<-18°C	1250	1.34	14
	RVF-202309V	2250*860*2000	2370*860*2080	<-18°C	1875	2.01	10
	RVF-203009V	3000*860*2000	3120*860*2080	<-18°C	2500	2.69	6
Cooling	RVD-201509V	1500*860*2000	1620*860*2080	-1°C~-5°C	1250	1.62	14
	RVD-202309V	2250*860*2000	2370*860*2080	-1°C~-5°C	1875	2.43	10
	RVD-203009V	3000*860*2000	3120*860*2080	-1°C~-5°C	2500	3.25	6

850 SERIES ISLAND FREEZER



model: IHF-D150SP IHF-D190SP IHF-D220SP IHF-D250SP
IHF-D150SPA IHF-D190SPA IHF-D220SPA IHF-D250SPA

Feature:

- Stable freezing, efficient preservation
- Reasonable design, convenient placement
- Hot gas defrosting for P series
- Big handle to be opened easily

Parameter:

Model	External dimensions/mm	Package dimensions/mm	Temperature range/°C	Gross volume/L	Display area/m ²	Stuffing quantity 40HC
IHF-D150SP	1430*860*860	1530*956*990	<-18°C	480	0.76	28
IHF-D190SP	1870*860*860	1940*956*990	<-18°C	560	0.96	24
IHF-D220SP	2150*860*860	2220*956*990	<-18°C	800	1.20	20
IHF-D250SP	2500*860*860	2570*956*990	<-18°C	950	1.42	16

Model	External dimensions/mm	Package dimensions/mm	Temperature range/°C	Gross volume/L	Display area/m ²	Stuffing quantity 40HC
IHF-D150SPA	1430*860*860	1530*956*990	<-18°C	480	0.76	28
IHF-D190SPA	1870*860*860	1940*956*990	<-18°C	560	0.96	24
IHF-D220SPA	2150*860*860	2220*956*990	<-18°C	800	1.20	20
IHF-D250SPA	2500*860*860	2570*956*990	<-18°C	950	1.42	16

830 SERIES ISLAND FREEZER



model: IHCF-D1908ECVA IHCF-D1908VA IHCF-D2008VA IHCF-D2508VA

Feature:

- Stable freezing, efficient preservation
- Reasonable design, convenient placement
- Up and down sliding door
- Interior LED, better to products display

Parameter:

Model	External dimensions/mm	Package dimensions/mm	Temperature range/°C	Gross volume/L	Display area/m ²	Stuffing quantity 40HC
IHCF-D1908ECVA	1860*830*700	1930*920*700	-20°C~7°C	577	1.09	24
IHCF-D1908VA	1860*830*845	1930*920*975	-20°C~7°C	640	1.09	24
IHCF-D2008VA	2000*830*845	2070*920*975	-20°C~7°C	687	1.23	24
IHCF-D2508VA	2500*830*845	2570*920*975	-20°C~7°C	892	1.5	16

SERVICE COUNTER



model: ICC-N14-K ICC-N20-K ICC-N26-K ICC-N39-K
ICC-N14V-K ICC-N20V-K ICC-N26V-K ICC-N39V-K

Feature:

- Transparent tempered glass
- Digital thermostat for exact temperature control
- LED lighting for better display
- Stable cooling for efficient preservation

Parameter:

Type	Model	External dimensions/mm	Package dimensions/mm	Temperature rate/°C	Gross volume/L	Display area/m ²	Stuffing quantity 40°C
Fresh meat plug in service counter	ICC-N14-K	1350*1100*910	1450*1190*1140	0°C-5°C	280	1.08	20
	ICC-N20-K	1970*1100*910	2070*1190*1140	0°C-5°C	410	1.56	20
	ICC-N26-K	2600*1100*910	2700*1190*1140	0°C-5°C	510	2.02	8
	ICC-N39-K	3850*1100*910	3950*1190*1140	0°C-5°C	710	3.08	6
Type	Model	External dimensions/mm	Package dimensions/mm	Temperature rate/°C	Gross volume/L	Display area/m ²	Stuffing quantity 40°C
Cooked food plug in service counter	ICC-N14V-K	1350*1100*910	1450*1190*1140	0°C-5°C	280	1.08	20
	ICC-N20V-K	1970*1100*910	2070*1190*1140	0°C-5°C	410	1.56	20
	ICC-N26V-K	2600*1100*910	2700*1190*1140	0°C-5°C	510	2.02	8
	ICC-N39V-K	3850*1100*910	3950*1190*1140	0°C-5°C	710	3.08	6


PLUG IN SEMI MULTIDECK



model: ISVM151509 ISVM151509A ISVM151509P

Feature:

- Removable glass door
- Low noise technology
- LED lighting for better display
- Stable cooling for efficient preservation



Parameter:

Type	Model	External dimensions/mm	Package dimensions/mm	Temperature rate/°C	Gross volume/L	Display area/m ²	Stuffing quantity 40°C
Inverter series	ISVM151509	3870*900*1500	2160*1050*1770	-1°C-5°C	690	2.36	11
Standard series	ISVM151509A	3870*900*1500	2160*1050*1770	-1°C-5°C	690	2.36	11
Glass door series	ISVM151509P	3870*900*1500	2160*1050*1770	-1°C-5°C	690	2.36	11

PLUG IN OPEN FRONT COOLER



model: RVD-2Z(C1WA/C2WA/C3WA)

Feature:

- Digital thermostat for exact temperature control
- Cyclic air to reduce heat exchange
- High-efficiency LED lighting
- Standard 4+1 shelves

Parameter:

Model	External dimensions/mm	Package dimensions/mm	Temperature rate/°C	Gross volume/L	Display area/m ²	Stuffing quantity 40HC
RVD-22C1WA	700*720*2020	760*760*2120	2°C~10°C	250	1.15	45
RVD-22C2WA	900*825*2045	920*880*2145	2°C~10°C	480	1.66	26
RVD-22C3WA	1160*825*2070	1220*880*2170	2°C~10°C	650	2.3	22

STORAGE FREEZER




model: HR-600 HF-600

Feature:

- High-efficiency compressor
- Digital thermostat for exact temperature control
- Both of cooling and freezing

Parameter:



Model	External dimensions/mm	Package dimensions/mm	Temperature rate/°C	Gross volume/L	Display area/㎡	Stuffing quantity 40%K
HR-600	780*690*1885	844*765*2094	0°C~10°C	574	0.90	42
HF-600	780*690*1885	844*765*2094	-18°C~-22°C	587	0.90	42

PLUG IN GLASS DOOR COOLER



model: IVC-211307A MC-211907A

Feature:

- Double insulating glass
- Adjustable shelf
- Interior LED light
- Automatic springback glass door

Parameter:

Model	External dimensions/mm	Package dimensions/mm	Temperature rate/°C	Gross volume/L	Display area/㎡	Stuffing quantity 40%K
IVC-211307A	1260*680*2130	1360*780*2230	0°C~10°C	900	1.70	25
MC-211907A	1860*680*2130	1960*780*2230	0°C~10°C	1600	2.60	18

SPECIFICATION

BEVERAGE COOLER

Model	SC-65	SC-85	SC-115	SC-9H-115	SC-106
Gross Volume	L 65	85	115	115	120
Net Volume	L 65	85	115	115	106
Gross Weight	Kg 30	34	40	40	40
Net Weight	Kg 27	30.5	35.5	35.5	35
Shelves Number	EA 1	2	2	2	2
Facing	330ml Can 5	5	5	5	5
Climate Class	/ ST	ST	N	N	ST
Temperature Range	°C 0°C-10°C	0°C-10°C	0°C-10°C	0°C-10°C	0°C-10°C
Refrigerant	/ R600a	R600a	R600a	R600a	R600a
Thermostat	/ Mechanical	Mechanical	Mechanical	Mechanical	Digital
External dimensions (W*D*H) mm	470*535*1465	530*595*1614-160	470*535*1614-160	470*535*1614-160	470*535*1614-160
Package dimensions (W*D*H) mm	530*595*1715	530*595*1865	530*595*1960	530*595*1960	530*595*1960
Stuffing quantity 40H	Set 258	258	172	172	160

Model	SC-346	SC-386	SC-336	SC-385	SC-281GA
Gross Volume	L 246	286	336	385	386
Net Volume	L 200	240	300	340	266
Gross Weight	Kg 54	57	66	78	60
Net Weight	Kg 48	50	58	69	53.5
Shelves Number	EA 3	4	4	4	3
Facing	330ml Can 7	7	7	8	7
Climate Class	/ ST	ST	ST	ST	ST
Temperature Range	°C 0°C-10°C	0°C-10°C	0°C-10°C	0°C-10°C	0°C-10°C
Refrigerant	/ R600a	R600a	R600a	R600a	R600a
Thermostat	/ Digital	Digital	Digital	Digital	Digital
External dimensions (W*D*H) mm	560*550*1349-251	625*625*1580	560*590*1310-253	645*638*1555	590*550*1310-253
Package dimensions (W*D*H) mm	621*628*1403	625*625*1580	625*625*1755	645*638*1555	590*550*1310-253
Stuffing quantity 40H	Set 104	57	57	51	57

Model	SC-380	SC-209	SC-229	SC-279	SC-329	SC-387
Gross Volume	L 320	209	229	279	329	387
Net Volume	L 306	209	229	279	329	387
Gross Weight	Kg 65	48	56	62	65	80
Net Weight	Kg 55.5	40	47	53	57	72.5
Shelves Number	EA 4	3	4	4	4	4
Facing	330ml Can 7	6	6	7	7	8
Climate Class	/ ST	ST	ST	ST	ST	N
Temperature Range	°C 0°C-10°C	0°C-10°C	0°C-10°C	0°C-10°C	0°C-10°C	0°C-10°C
Refrigerant	/ R600a	R600a	R600a	R600a	R600a	R600a
Thermostat	/ Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
External dimensions (W*D*H) mm	590*550*1300	520*550*1215	520*550*1310	590*550*1310	590*550*1310	660*550*1310
Package dimensions (W*D*H) mm	652*624*2032	582*624*1747	582*624*1842	652*624*1927	652*624*2032	726*626*2136
Stuffing quantity 40H	Set 57	106	104	76	76	51

Model	SC-209E	SC-229E	SC-279E	SC-329E	SC-389	SC-281C	SC-381C
Gross Volume	L 209	229	279	329	389	280	320
Net Volume	L 209	229	279	329	389	280	320
Gross Weight	Kg 48	56	62	65	65	60	66
Net Weight	Kg 42	53	58	60	60	55.5	58.5
Shelves Number	EA 3	3	4	4	4	3	4
Facing	330ml Can 6	6	7	7	7	7	7
Climate Class	/ ST	ST	ST	ST	ST	ST	N
Temperature Range	°C 0°C-10°C	0°C-10°C	0°C-10°C	0°C-10°C	0°C-10°C	0°C-10°C	0°C-10°C
Refrigerant	/ R600a	R600a	R600a	R600a	R600a	R600a	R600a
Thermostat	/ Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
External dimensions (W*D*H) mm	520*550*1157	520*550*1252	590*550*1317	590*550*1317	590*550*1317	590*550*1317	590*550*1317
Package dimensions (W*D*H) mm	582*624*1589	582*624*1684	652*624*1769	652*624*1874	652*624*2020	652*624*1927	652*624*2032
Stuffing quantity 40H	Set 106	104	76	76	57	57	57

SPECIFICATION

Model	SC-396	SC-398	SC-400	SC-528	SC-606	SC-360A
Gross Volume	L 386	388	435	528	606	345
Net Volume	L 386	388	400	528	606	320
Gross Weight	Kg 104	104	108	129	146	60
Net Weight	Kg 94	94	98	118	135	55
Shelves Number	EA 4	4	4	4	4	4
Facing	330ml Can 8	8	8	10	12	7
Climate Class	/ ST	ST	T	T	ST	ST
Temperature Range	°C 0°C-10°C	0°C-10°C	0°C-10°C	0°C-10°C	0°C-10°C	2°C-4°C
Refrigerant	/ R290	R290	R290	R290	R290	R290
Thermostat	/ Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	Digital
External dimensions (W*D*H) mm	600*662*2120	600*662*2220	660*680*2135	790*752*2294	890*890*2284	600*560*1915
Package dimensions (W*D*H) mm	725*755*2160	725*755*2260	725*765*2165	857*757*2315	967*783*2320	650*610*1880
Stuffing quantity 40H	Set 48	48	48	42	35	76

Model	SC-310NA	SC-360NA	SC-400NA	SC-400NA	SC-510	SC-540
Gross Volume	L 311	385	330	425	545	575
Net Volume	L 280	320	453	400	510	540
Gross Weight	Kg 56	57	73	99	110	130
Net Weight	Kg 51	52	65	88	96	122
Shelves Number	EA 4	4	4	4	6	6
Facing	330ml Can 7	7	7	8	8	9
Climate Class	/ ST	ST	T	T	T	T
Temperature Range	°C 2°C-8°C	2°C-8°C	2°C-8°C	0°C-10°C	0°C-10°C	0°C-10°C
Refrigerant	/ 134a	134a	134a	134a	134a	134a
Thermostat	/ Digital	Digital	Digital	Digital	Digital	Digital
External dimensions (W*D*H) mm	600*565*1540	600*565*1730	610*724*1845	600*681*1869	680*677*2098	735*685*2145
Package dimensions (W*D*H) mm	650*610*1700	650*610*1790	660*715*1910	725*780*1960	741*759*2112	825*760*2240
Stuffing quantity 40H	Set 77	76	69	47	48	42

Model	SC-630	SC-760	SC-62A	SC-62A	SC-120A	SC-178A
Gross Volume	L 645	805	40	60	130	178
Net Volume	L 620	760	34	53	126	168
Gross Weight	Kg 134	158	42	52	75	85
Net Weight	Kg 124	148	32	40	68	76
Shelves Number	EA 7	3	3	2	2	3
Facing	330ml Can 9	12	4	4	6	6
Climate Class	/ ST	T	T	T	T	T
Temperature Range	°C 0°C-10°C	0°C-10°C	0°C-12°C	0°C-12°C	0°C-12°C	0°C-12°C
Refrigerant	/ 134A	134A	R600a	R600a	R600a	R600a
Thermostat	/ Digital	Digital	Digital/thermostat	Digital/thermostat	Digital/thermostat	Digital/thermostat
External dimensions (W*D*H) mm	735*627*2137	897*652*2117	370*426*930	370*426*930	500*552*1210	500*552*1323
Package dimensions (W*D*H) mm	862*738*2130	652*626*2100	440*476*700	440*476*700	570*605*1170	570*605*1383
Stuffing quantity 40H	Set 42	36	665	399	156	78

Model	SC-219A	SC-160W	SC-260D	SC-260	SC-409	SC-609
Gross Volume	L 240	375	160	320	409	609
Net Volume	L 230	160	260	260	409	609
Gross Weight	Kg 88	62	64	64	104	153
Net Weight	Kg 80	59	56	56	88	120
Shelves Number	EA 4	5	4	4	6	6
Facing	330ml Can 6	4	5	5	10	14
Climate Class	/ ST	ST	T	T	N	N
Temperature Range	°C 0°C-12°C	0°C-12°C	0°C-10°C	0°C-10°C	0°C-10°C	0°C-12°C
Refrigerant	/ R600a/R290	R134a/R290	R600a	R600a	R290	R290
Thermostat	/ Digital/thermostat	Mechanical	Mechanical	Mechanical	Digital	Digital
External dimensions (W*D*H) mm	500*535*1600	390*480*1885	470*570*1864-253	470*570*1993	880*887*1897	1180*887*1983
Package dimensions (W*D*H) mm	570*605*1670	460*530*1920	530*670*1940	530*670*2064	1000*650*2052	1290*650*2132
Stuffing quantity 40H	Set 78	139	66	66	41	27

SPECIFICATION

Model	SC-80S	SC-80H	SC-120H	SC-100H	SC-800H	SC-800SA
Gross Volume	L 809	850	1200	1006	800	800
Net Volume	L 809	800	1200	1006	780L	673
Gross Weight	Kg 173	142	203	192	135	135
Net Weight	Kg 148	121	178	170	120	120
Shelves Number	EA 6	6	9	10	8	8
Facing	330m) Can 16	14	21	16	12	12
Climate Class	/	ST	ST	N	ST	N
Temperature Range	°C 0°C~10°C	0°C~10°C	0°C~10°C	0°C~10°C	0°C~10°C	0°C~10°C
Refrigerant	/	R290	R290	R134A/R290	R134A/R290	R134A/R290
Thermostat	/	Digital	Digital	Digital	Digital	Digital
External dimensions (W*D*H)	mm 1430*651*1803	1180*623*2000	1780*628*2000	1200*1112*2200	1000*680*2000	1000*660*2000
Package dimensions (W*D*H)	mm 1540*750*2052	1260*722*2105	1890*722*2105	1275*782*2430	1045*685*2085	1045*685*2085
Stuffing quantity 40H	Set 22	27	19	24	33	33

Model	SC-1000HA	SC-1000SA	SC-1100HA	SC-1000SA	SC-1200HA	SC-1200SA
Gross Volume	L 1000	1000	1100	1100	1200	1200
Net Volume	L 879	772	954	823	1074	943
Gross Weight	Kg 154	154	154	154	154	154
Net Weight	Kg 124	124	129	139	139	139
Shelves Number	EA 8	8	8	8	8	8
Facing	330m) Can 12	12	14	14	14	14
Climate Class	/	N	N	N	N	N
Temperature Range	°C 0°C~10°C	0°C~10°C	0°C~10°C	0°C~10°C	0°C~10°C	0°C~10°C
Refrigerant	/	R134A/R290	R134A/R290	R134A/R290	R134A/R290	R134A/R290
Thermostat	/	Digital	Digital	Digital	Digital	Digital
External dimensions (W*D*H)	mm 1000*730*2020	1000*730*2020	1200*680*2020	1200*680*2020	1200*730*2020	1200*680*2020
Package dimensions (W*D*H)	mm 1045*775*2085	1045*775*2085	1245*782*2085	1245*685*2085	1245*775*2085	1245*685*2085
Stuffing quantity 40H	Set 33	33	28	28	27	28

Model	SC-1300HA	SC-1300SA	SC-1400HA	SC-1400SA	SC-1600HA
Gross Volume	L 1300	1300	1400	1400	1800
Net Volume	L 1101	996	1245	1093	1600
Gross Weight	Kg 180	180	180	180	280
Net Weight	Kg 145	145	145	145	262
Shelves Number	EA 8	8	8	8	12
Facing	330m) Can 16	16	16	16	21
Climate Class	/	N	N	N	N
Temperature Range	°C 0°C~10°C	0°C~10°C	0°C~10°C	0°C~10°C	0°C~10°C
Refrigerant	/	R134A/R290	R134A/R290	R134A/R290	R134A/R290
Thermostat	/	Digital	Digital	Digital	Digital
External dimensions (W*D*H)	mm 1375*660*2020	1375*660*2020	1375*750*2020	1375*750*2020	1800*730*2020
Package dimensions (W*D*H)	mm 1420*685*2085	1420*685*2085	1420*775*2085	1420*775*2085	1845*750*2085
Stuffing quantity 40H	Set 24	24	24	24	19

COMMERCIAL FREEZER

Model	SD-289	SD-359	SD-439	SD-519	SD-152	SD-180
Gross Volume	L 289	359	439	519	152	180
Net Volume	L 202	249	322	360	110	122
Gross Weight	Kg 67	78	86	95	53	49
Net Weight	Kg 58	68	75	85	46	43
Baskets Number	EA 4	5	6	6	2	3
Climate Class	/	ST	ST	ST	ST	ST
Temperature Range	°C -10°C~ -30°C	-10°C~ -30°C	-10°C~ -30°C	-10°C~ -30°C	-10°C~ -30°C	-10°C~ -30°C
Refrigerant	/	R134a	R134a	R134a	R290	R600a
Thermostat	/	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
External dimensions (W*D*H)	mm 348*498*590	322*498*590	348*598*590	348*698*590	584*498*590	584*598*590
Package dimensions (W*D*H)	mm 1127*717*1009	1307*717*1009	1571*717*1009	1698*717*1041	662*772*1022	835*730*1010
Stuffing quantity 40H	Set 90	81	63	42	108	126

SPECIFICATION

Model	SD-290	SD-330	SD-338HA	SD-430	SD-530	SD-100F
Gross Volume	L 289	330	338	430	530	100
Net Volume	L 177	214	256	275	345	77
Gross Weight	Kg 57	71	85	85	95	38
Net Weight	Kg 51	63	73	76	85	35
Baskets Number	EA 4	5	5	5	7	1
Climate Class	/	ST	ST	ST	ST	ST
Temperature Range	°C -10°C~ -30°C	-10°C~ -30°C	-10°C~ -30°C	-10°C~ -30°C	-10°C~ -30°C	-10°C~ -20°C
Refrigerant	/	R290	R290	R290	R290	R600a
Thermostat	/	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
External dimensions (W*D*H)	mm 380*550*716	1224*654*925	1224*654*925	1315*698*939	1465*928*916	600*522*825
Package dimensions (W*D*H)	mm 1300*730*900	1300*730*900	1300*730*900	1300*730*900	1740*770*930	660*542*985
Stuffing quantity 40H	Set 99	81	54	72	57	215

Model	SD-200F	SD-300F	SD-400F	SD-500F	SD-600F	SD-40WTF
Gross Volume	L 200	300	400	500	600	426
Net Volume	L 156	215	275	337	400	286
Gross Weight	Kg 49	63	72	82	91	127
Net Weight	Kg 45	56	65	73	81	114
Baskets Number	EA 1	1	1	1	1	5
Climate Class	/	ST	ST	ST	ST	ST
Temperature Range	°C -10°C~ -20°C	-10°C~ -20°C	-10°C~ -20°C	-10°C~ -20°C	-10°C~ -20°C	-10°C~ -30°C
Refrigerant	/	R600a	R134a	R290	R290	R290
Thermostat	/	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
External dimensions (W*D*H)	mm 934*574*825	1014*604*825	1222*694*825	1434*694*825	1664*694*825	1255*796*1025
Package dimensions (W*D*H)	mm 994*634*885	1094*714*885	1302*774*885	1514*774*885	1744*774*885	1335*751*1130
Stuffing quantity 40H	Set 108	95	81	72	57	42

Model	SD-536T	SD-596	SD-506	SD-561	SD-661	SD-761
Gross Volume	L 536	596	506	561	661	761
Net Volume	L 385	316(323+384)	405	372(233)	411	479
Gross Weight	Kg 122	96	140	144	115	121
Net Weight	Kg 112	76	118	124	94	109
Baskets Number	EA 6	3	5	6	6	6
Climate Class	/	ST	ST	ST	ST	ST
Temperature Range	°C -10°C~ -30°C	8°C~ -30°C	8°C~ -30°C	8°C~ -30°C	-10°C~ -30°C	-10°C~ -30°C
Refrigerant	/	R290	R290	R290	R290	R290
Thermostat	/	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
External dimensions (W*D*H)	mm 1560*840*1025	992*780*1896	1234*780*1896	1651*811*786	1871*811*786	1651*931*786
Package dimensions (W*D*H)	mm 1575*965*1130	1010*822*1985	1344*822*1985	1705*875*930	1925*875*930	1705*1075*940
Stuffing quantity 40H	Set 28	28	22	28	24	28

Model	SD-1021	SD-602	SD-702	SD-532	SD-570	SD-528
Gross Volume	L 1021	602	702	532	570	528
Net Volume	L 715	415	445	364	425	381
Gross Weight	Kg 175	111	115	113	112	112
Net Weight	Kg 145	99	101	103	104	97
Baskets Number	EA 8	6	6	6	6	6
Climate Class	/	ST	ST	ST	ST	ST
Temperature Range	°C -10°C~ -30°C	-10°C~ -30°C	-10°C~ -30°C	-10°C~ -30°C	-10°C~ -30°C	-10°C~ -30°C
Refrigerant	/	R290	R290	R290	R290	R290
Thermostat	/	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
External dimensions (W*D*H)	mm 2051*1017*940	1895*790*777	1895*790*777	1871*917*913	1877*917*908	1877*917*908
Package dimensions (W*D*H)	mm 2105*1075*1045	2008*891*905	2008*891*905	1923*869*1060	1923*869*1005	1923*869*965
Stuffing quantity 40H	Set 20	26	26	24	24	24

SPECIFICATION

Model	SD-20Q	SD-27Q	SD-35Q	SD-45Q	SD-55Q	SD-65Q	SDQ-70
Gross Volume	L 545	615	599	400	500	600	700
Net Volume	L 427	480	273	355	445	545	645
Gross Weight	Kg 81	101	64	73	84	93	104
Net Weight	Kg 75	91	58	65	75	82	92
Baskets Number	EA 6	7	3	4	5	6	7
Climate Class	/	N	N	N	N	N	N
Temperature Range	/	-10°C ~ -30°C	-10°C ~ -30°C	-10°C ~ -30°C	-10°C ~ -30°C	-10°C ~ -30°C	-10°C ~ -30°C
Refrigerant	/	R134A	R134A	R134A/R290	R134A/R290	R404A/R290	R404A/R290
Thermostat	/	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
External dimensions (W*D*H)	mm 1810*680*850	2000*675*850	1000*695*850	1250*695*850	1500*695*850	1750*695*850	2000*695*850
Package dimensions (W*D*H)	mm 1800*780*890	2000*770*890	1050*780*890	1300*780*890	1550*780*890	1800*780*890	2050*780*890
Stuffing quantity 40'H	Set 56	51	38	40	46	54	60

Model	SD-57S	SD-72S	SD-100	SD-138	SDQ-160S	SDQ-400S
Gross Volume	L 575	728	100	108	150	400
Net Volume	L 391	516	100	290	148	380
Gross Weight	Kg 145	155	60	144	75	150
Net Weight	Kg 124	132	51	126	68	140
Baskets Number	EA 6	6	2	4	5	5
Climate Class	/	ST	N	N	N	N
Temperature Range	/	-10°C ~ -30°C	-10°C ~ -30°C	-18°C ~ -28°C	-18°C ~ -22°C	-18°C ~ -22°C
Refrigerant	/	R290	R290	R404A	R290	R290
Thermostat	/	Mechanical	Mechanical	Digital	Digital	Digital
External dimensions (W*D*H)	mm 1997*1023*788	1997*1023*788	600*695*940	660*701*1210	390*505*1885	670*665*2010
Package dimensions (W*D*H)	mm 2047*1069*885	2047*1069*1060	650*700*1050	725*755*2217	440*330*2100	700*655*2030
Stuffing quantity 40'H	Set 31	22	304	48	139	51

Model	SD-1000	SDQ-160M	SDQ-22Q	SDQ-27Q	SDQ-42Q	SDQ-20Q
Gross Volume	L 1000	1000	100	273	278	445
Net Volume	L 705	1400	136	212	278	355
Gross Weight	Kg 200	240	58	60.5	69	72.5
Net Weight	Kg 187	235	54	56	62.5	65.5
Baskets Number	EA 6	15	2	3	4	5
Climate Class	/	N	N	N	N	N
Temperature Range	/	-18°C ~ -22°C	-18°C ~ -22°C	-18°C ~ -30°C	-18°C ~ -30°C	-18°C ~ -30°C
Refrigerant	/	R290	R134A	R134A	R134A	R134A
Thermostat	/	Digital	Digital	Mechanical	Mechanical	Mechanical
External dimensions (W*D*H)	mm 1220*665*2010	1800*730*2020	740*680*850	1030*680*850	1270*680*850	1530*680*850
Package dimensions (W*D*H)	mm 1250*655*2030	1840*755*2085	790*780*890	1080*780*890	1320*780*890	1580*780*890
Stuffing quantity 40'H	Set 27	16	134	48	79	65

SUPERMARKET FREEZER

Model	RVM-201309V	RVM-201909	RVM-202509V	RVM-203809V	RVM-201709EC	RVM-201309V
Gross Volume	L 900	1350	1800	2700	1220	900
Net Volume	L 710	1050	1400	2100	950	710
Gross Weight	Kg 230	330	420	620	305	295
Net Weight	Kg 210	300	380	560	280	275
Climate Class	/	N	N	N	N	N
Temperature Range	/	-18°C ~ -5°C	-18°C ~ -5°C	-18°C ~ -5°C	-18°C ~ -5°C	-18°C ~ -5°C
Refrigerant	/	404A	404A	404A	404A	404A
Thermostat	/	Digital	Digital	Digital	Digital	Digital
External dimensions (W*D*H)	mm 1250*850*870*2000	1875*850*870*2000	2500*850*870*2000	3750*850*870*2000	1700*850*870*2000	1250*850*870*2000
Package dimensions (W*D*H)	mm 1310*910*960*2080	1965*910*960*2080	2600*910*960*2080	3810*910*960*2080	1820*910*960*2080	1370*910*960*2080
Stuffing quantity 40'H	Set 17	12	8	6	13	17

SPECIFICATION

Model	RVM-201909V	RVM-202509V	RVM-203809V	RVM-201709ECV	RVF-201509V	RVF-202309V
Gross Volume	L 1350	1800	2700	1220	1250	1875
Net Volume	L 1100	1500	2200	1050	1050	1550
Gross Weight	Kg 440	550	800	400	250	425
Net Weight	Kg 410	510	740	375	260	380
Climate Class	/	N	N	N	N	N
Temperature Range	/	-18°C ~ -5°C	-18°C ~ -5°C	-18°C ~ -5°C	-18°C ~ -5°C	-18°C ~ -5°C
Refrigerant	/	404A	404A	404A	404A	404A
Thermostat	/	Digital	Digital	Digital	Digital	Digital
External dimensions (W*D*H)	mm 1875*850*870*2000	2500*850*870*2000	3750*850*870*2000	1700*850*870*2000	1500*850*870*2000	2250*850*870*2000
Package dimensions (W*D*H)	mm 1935*910*990*2080	2620*910*990*2080	3870*910*990*2080	1820*910*990*2080	1620*910*990*2080	2370*910*990*2080
Stuffing quantity 40'H	Set 12	8	6	13	14	10

Model	RVF-203009V	RVD-201509V	RVD-203309V	RVD-203009V	ICC-N14-K	ICC-N20-K
Gross Volume	L 2500	1250	1870	2500	280	410
Net Volume	L 2100	1050	1550	2100	240	350
Gross Weight	Kg 540	270	395	500	200	210
Net Weight	Kg 480	240	350	440	170	180
Climate Class	/	N	N	N	N	N
Temperature Range	/	-18°C ~ -5°C	-18°C ~ -5°C	-18°C ~ -5°C	-18°C ~ -5°C	-18°C ~ -5°C
Refrigerant	/	404A	404A	404A	404A	404A
Thermostat	/	Digital	Digital	Digital	Digital	Digital
External dimensions (W*D*H)	mm 3000*860*2000	1500*860*2000	2250*860*2000	3000*860*2000	1350*1100*1140	1870*1100*1140
Package dimensions (W*D*H)	mm 3120*880*2080	1620*880*2080	2370*880*2080	3120*880*2080	1450*1190*1140	2070*1190*1140
Stuffing quantity 40'H	Set 6	14	10	6	20	20

Model	ICC-N26-K	ICC-N39-K	ICC-N14V-K	ICC-N20V-K	ICC-N26V-K	ICC-N39V-K
Gross Volume	L 530	710	280	410	510	710
Net Volume	L 470	650	240	350	440	620
Gross Weight	Kg 260	420	210	260	300	410
Net Weight	Kg 220	360	180	220	260	420
Climate Class	/	N	N	N	N	N
Temperature Range	/	-18°C ~ -5°C	-18°C ~ -5°C	-18°C ~ -5°C	-18°C ~ -5°C	-18°C ~ -5°C
Refrigerant	/	404A	404A	404A	404A	404A
Thermostat	/	Digital	Digital	Digital	Digital	Digital
External dimensions (W*D*H)	mm 2600*1100*1140	3850*1100*1140	1350*1100*1140	1970*1100*1140	2600*1100*1140	3850*1100*1140
Package dimensions (W*D*H)	mm 2700*1190*1140	3950*1190*1140	1450*1190*1140	2070*1190*1140	2700*1190*1140	3950*1190*1140
Stuffing quantity 40'H	Set 108	95	6	20	578	6

Model	ISVM151909	ISVM151909A	ISVM151909P	VD-191008	VD-191908	ISVD-150706
Gross Volume	L 690	690	690	451	900	169
Net Volume	L 570	570	570	380	750	140
Gross Weight	Kg 330	330	330	160	270	330
Net Weight	Kg 310	310	310	140	247	310
Climate Class	/	N	N	N	N	N
Temperature Range	/	-18°C ~ -5°C	-18°C ~ -5°C	-18°C ~ -5°C	-18°C ~ -5°C	-18°C ~ -5°C
Refrigerant	/	404A	404A	404A	404A	404A
Thermostat	/	Digital	Digital	Digital	Digital	Digital
External dimensions (W*D*H)	mm 1870*900*1500	1870*900*1500	1870*900*1500	997*750*1500	1957*750*1500	700*600*1500
Package dimensions (W*D*H)	mm 2160*1050*1770	2160*1050*1770	2160*1050*1770	1096*820*1660	2052*820*1660	790*630*1660
Stuffing quantity 40'H	Set 11	11	11	18	14	49

SPECIFICATION

OUR GLOBAL PARTNERS

Model	RVD-22C19A	RVD-22C24A	RVD-22C39A	HF-600	HF-600	HF-11307A	HF-21307A
Gross Volume	L 350L	400L	650L	600	600	1000	1370
Net Volume	L /	/	/	574	587	900	1600
Gross Weight	Kg 150	225	250	186	206	157	233
Net Weight	Kg 130	206	230	165	189	136	205
Climate Class	/	N	N	N	N	ST	ST
Temperature Range	/ °C 2-10°C	2-10°C	2-10°C	0°C-10°C	-18°C ~ -22°C	0°C-10°C	0°C-10°C
Refrigerant	/	404A	404A	R600a	R290	R134a	R134a
Thermostat	/	Digital	Digital	Digital	Digital	Digital	Digital
External dimensions (W*D*H)	mm 700*720*2020	900*825*2045	1160*825*2070	780*696*1885	780*696*1885	1260*680*2130	1860*680*2130
Package dimensions (W*D*H)	mm 760*760*2120	920*880*2145	1220*880*2170	844*765*2094	844*765*2094	1360*780*2130	1860*780*2230
Stuffing quantity 40H	Set 45	26	23	42	42	25	18

Model	HF-D1509P	HF-D1909P	HF-D2209P	HF-D2509P	HF-D1509PA	HF-D1909PA
Baskets Number	4	4	6	7	4	4
Gross Volume	L 566	700	930	1080	566	700
Net Volume	L 480	560	800	950	480	560
Gross Weight	Kg 124	139	155	185	124	139
Net Weight	Kg 104	119	135	165	104	119
Baskets Number	EA 4	4	6	7	4	4
Climate Class	/	N	N	N	N	N
Temperature Range	/ °C	<18°C	<18°C	<18°C	<18°C	<18°C
Refrigerant	/	R290	R290	R404a	R290	R290
Thermostat	/	Digital	Digital	Digital	mechanical	mechanical
External dimensions (W*D*H)	mm 1430*860*860	1870*860*860	2150*860*860	2500*860*860	1430*860*860	1870*860*860
Package dimensions (W*D*H)	mm 1530*960*990	1940*960*990	2220*960*990	2570*960*990	1530*960*990	1940*960*990
Stuffing quantity 40H	Set 28	24	20	16	28	24

Model	HF-D2209PA	HF-D2509PA	HF-D1908EVA	HF-D1908VA	HF-D2008VA	HF-D2508VA
Baskets Number	6	7	4	4	6	7
Gross Volume	L 910	1080	702	765	812	1017
Net Volume	L 800	950	577	640	687	892
Gross Weight	Kg 155	185	124	139	155	185
Net Weight	Kg 135	165	104	119	135	165
Baskets Number	EA 6	7	4	4	6	7
Climate Class	/	N	N	N	N	N
Temperature Range	/ °C	<18°C	<18°C	-20°C ~ -7°C	-20°C ~ -7°C	-20°C ~ -7°C
Refrigerant	/	R290	R290	R290	R290	R290
Thermostat	/	mechanical	mechanical	mechanical	mechanical	mechanical
External dimensions (W*D*H)	mm 2150*860*860	2500*860*860	1865*830*790	1865*830*845	2000*830*845	2500*830*845
Package dimensions (W*D*H)	mm 2220*950*990	2570*950*990	1935*920*920	1935*920*975	2070*920*975	2570*920*975
Stuffing quantity 40H	Set 20	16	24	24	24	16

Aucma commercial refrigeration partnered with 8000 drinks & food companies, including Coca-Cola, Carlsberg, Nestle, Haagen-Dazs, AB-Inbev, Unilever, Aice etc. Also good business relationship with domestic leading brands, such as Nongfu Spring, Uni-President, Yili, Yuanqi Forest, etc.

To be the most trustworthy refrigeration expert of the world, Aucma will firmly stick to the professionalism and flexibility in commercial refrigeration field to provide best stability and reliability to our partners.

